

Silver and Copper Corrosion Bath

ASTM D130; D4048; D4814; D7667; D7671; BS 2000-154; ISO 2160; IP 154; 611

- Maximum capacity of 27 tubes
- Programmable digital temperature controller
- Thermometer port
- Digital timer

The bath is a stainless steel water or oil bath, digitally controlled to ± 0.1 °C over a temperature range of ambient +5 °C to 150 °C, used to determine the corrosive effects of fuels, lubricants and other hydrocarbon products on copper and silver.

The bath has nine test stations, each with a lid and hook for suspending either a Corrosion Pressure Vessel (11500-0) or a test tube Support Assembly (11420-0). The test tube support can hold up to three Test Tubes (11590-0). You can use any combination of copper corrosion vessels and test tube supports.

Supplied with; 9 x lids, mains lead, instruction manual.



Specifications:

Product Number:	11400-7
Temperature Range:	Ambient +5 to 150°C
Stability:	± 0.1 °C
Bath Fluid:	Water or Oils
Bath Capacity:	34 litres
Heater Power:	150W
Water Inlet Nozzle:	10 mm
Overflow Drain:	10 mm
Voltage:	110/120 V, 60 Hz 220/240 V, 50 Hz
Size (HxWxD):	52 x 45 x 33 cm
Weight:	10 kg