ASTM D130; ASTM D4048; ASTM D4814; ASTM D7667; ASTM D7671; IP 112; IP 154; IP 611; BS2000-112; BS2000-154; BS EN ISO 2160

- Maximum capacity of 6 test stations
- Precise temperature control

SETA STANHOPE-SETA

- Digital timer
- Over temperature cut out and liquid level float switch
- Maximum liquid level outlet fitting
- Small footprint

The Seta Silver and Copper Corrosion Bath is a bench top, stainless steel water or oil bath. Digitally controlled to ± 0.1 °C over a temperature range of ambient ± 5 °C to 150 °C, the bath is used to determine the corrosive effects of fuels, lubricants and other hydrocarbon products on copper and silver.

The bath features 6 test stations, each with a lid and hook for suspending a Corrosion Pressure Vessel (11500-0) or a test tube Support Assembly (11422-0). You can use any combination of copper corrosion vessels and test tube supports for maximum test flexibility.

Supplied with; 6 x lids, mains lead, instruction manual.



Specifications:	
Product Number:	11405-0
Temperature Range:	Ambient +5 to 150 °C
Stability:	±0.1 °C
Bath Fluid:	Water or Oil
Bath Capacity:	22 litres
Apertures:	6 x 52 mm
Heater Power:	1500 W
Voltage:	110/120 V, 50/60 Hz 200/240 V, 50/60 Hz
Size (HxWxD):	51 x 23 x 46 cm
Weight:	13.3 kg